HIQ FAQ

Features

Can I connect a water detector for leakages?

A water detector features digital output and can be connected to a free input on LC-10-IQ light controller.

Indication may be transmitted on one (or all) of the following ways:

- The appropriate output can be connected to actuator which closes the water in the whole house/apartment.
- Indication with a horn/light (or a scene) which is linked to an appropriate output.
- Connection with home alarm.
- Connection with GSM modem that sends SMS and/or make a telephone call

What if the sensor has an analogue output 0-10V?

Analogue sensors are not supported as standard and you need a custom programming. Home controller already includes 4 8-bit analogue inputs and if you need a higher accuracy AD module can be added to the system.

Hardware

I would like to check and set the temperature of hot domestic water with my smartphone. How can I do that and what type of equipment do I need?

You need one of thermostats to which you connect additional external sensor (ES-IQ or ES-A-IQ) which is installed in/on the water heater. Combination is then configured in HIQ Configurator and water temperature is controlled in the same way as the temperature in a room.

Software

I have an oil heater. During the transitional period (in spring and autumn) I would like that it operates only for one hour in the morning and for two hours in the evening. What kind of custom programming do I need?

No additional programming is needed. You should connect the oil heater power supply to one of free outputs on LC-10-IQ light controller. Then you use a free timetable in HIQ configurator

and set appropriate output (or you combine it with a scene and/or thermostat-s).

From: http://wiki.hiq-universe.com/ -

Permanent link: http://wiki.hiq-universe.com/doku.php?id=en:hiq_home:faq&rev=1538747328



Last update: 2018/10/05 13:48