

Electric strike

Electromechanical strike lock



<WRAP column 500px>

| | | |
|---------------|--------------|-----------------|
| Model number: | EL-ST | Electric strike |
| Mounting: | Field, | on door frame |


General description

The most compact electric strike without sacrificing any of the quality or safety offered by our other products. EL-ST is the perfect match for narrow aluminium, PVC or timber profiles.

Technical specifications

| | |
|---|--------------------------------------|
| Power supply: | 9-24V AC/DC, 12V DC |
| Continuos duty: | <1 min/ED 100% |
| Rated resistance: | 43 Ohm |
| Current consumption AC: | 0.15A...9V, 0.2A...12V, 0.39A...24V |
| Current consumption DC(stabilized): | 0.21A...9V, 0.28A...12V, 0.56A...24V |
| Maximum side-load on AC: | 24V - 200N |
| Maximum side-load on DC (stabilized): | 12V - 50N |
| Break-in resistance: | 4.800N |
| Dynamic strength: | 4.400N |
| Endurance rating (cycles no side-load): | 200.000 |
| Complies with the directive: | 2014/30/UE; 2011/65/UE |

Dimensions



From:
<http://wiki.hiq-universe.com/> -

Permanent link:
http://wiki.hiq-universe.com/doku.php?id=en:hiq_hw:el_strike&rev=1623320276

Last update: **2021/06/10 10:17**

