

# Electric strike

## Electromechanical strike lock

|               |                      |                 |
|---------------|----------------------|-----------------|
| Model number: | <b>EL-ST</b>         | Electric strike |
| Mounting:     | Field, on door frame |                 |



## General description

The most compact electric strike without sacrificing any of the quality or safety offered by our other products. EL-ST is the perfect match for narrow aluminium, PVC or timber profiles.

## Technical specifications

|                                       |                                      |
|---------------------------------------|--------------------------------------|
| Power supply:                         | 9-24V AC/DC, 12V DC                  |
| Continuos duty:                       | <1 min/ED 100%                       |
| Rated resistance:                     | 43 Ohm                               |
| Current consumption AC:               | 0.15A...9V, 0.2A...12V, 0.39A...24V  |
| Current consumption DC(stabilized):   | 0.21A...9V, 0.28A...12V, 0.56A...24V |
| Maximum side-load on AC:              | 24V - 200N                           |
| Maximum side-load on DC (stabilized): | 12V - 50N                            |
| Break-in resistance:                  | 4.800N                               |
| Dynamic strength:                     | 4.400N                               |

|   |                        |
|---|------------------------|
| Endurance rating (cycles no side-load): | 200.000                |
| Complies with the directive:            | 2014/30/UE; 2011/65/UE |

## Dimensions



From:  
<http://wiki.hiq-universe.com/> -

Permanent link:  
[http://wiki.hiq-universe.com/doku.php?id=en:hiq\\_hw:el\\_strike&rev=1623320585](http://wiki.hiq-universe.com/doku.php?id=en:hiq_hw:el_strike&rev=1623320585)

Last update: **2021/06/10 10:23**

