







# Soft remote

## Enocean wireless soft remote



Model number:		<b>EN-SR-WT-IQ</b>
		<b>EN-SR-BL-IQ</b>
		<b>EN-SR-GY-IQ</b>
		<b>EN-SR-GN-IQ</b>
		<b>EN-SR-MG-IQ</b>
		<b>EN-SR-CY-IQ</b>
Mounting:	In-field; remote	
Dimensions:	56 x 56 x 20 mm	
Connection:	Wireless Enocean	
	<a href="#">MC-230-01</a>	
	<a href="#">MC-230-03</a>	
	<a href="#">MC-24-01</a>	
	<a href="#">MC-24-03</a>	
	<a href="#">MC-24-05</a>	

- No battery

- Wireless
- Shock proof, Spill resistant, Magnetic

## Technical specifications

Power supply:	Magneto-resistive (no battery)
Buttons/channels:	2 / 4
Range:	Up to 30m indoor
Operational temperature:	0°C to 40°
EEP (EnOcean Profile):	F6-02-02
Dimensions :	56 x 56 x 20 mm

## Certifications and standards

### Europe

- EN 60950-1:2006+A11:2009+
- A1:2010+A12:2011+A2:2013
- EN 301489-3 V1.6.1
- EN 61000-3-2:2013,
- EN 61000-3-3:2013
- EN 300220-2:V3.1.1
- EN 62479:2010

### USA

- FCC & IC Rules

From:

<http://wiki.hiq-universe.com/> -

Permanent link:

[http://wiki.hiq-universe.com/doku.php?id=en:hiq\\_hw:en-sr-ig&rev=1566290481](http://wiki.hiq-universe.com/doku.php?id=en:hiq_hw:en-sr-ig&rev=1566290481)

Last update: **2019/08/20 08:41**

