


# Wall switch

## Enocean wireless wall switch



Model number:		<b>PB-WE-W1</b>
Mounting:	In-field; on wall	
Dimensions:	80 x 80 x 15 mm	
Connection:	Wireless Enocean	
	<a href="#">MC-230-01</a>	
	<a href="#">MC-230-03</a>	
	<a href="#">MC-24-01</a>	
	<a href="#">MC-24-03</a>	
		<a href="#">MC-24-05</a>

- No battery
- Wireless
- Easy to mount
- Pleasant press
- Customizable

## Technical specifications

Power supply:	Magneto-resistive (no battery)
Buttons/channels:	2 / 4 or 1 / 1
Range:	Up to 30m indoor
Operational temperature:	0°C to 40°
EEP (EnOcean Profile):	F6-02-01
Dimensions :	80 x 80 x 15 mm

## Certifications and standards

### Europe

- EN 60950-1:2006+A11:2009+
- A1:2010+A12:2011+A2:2013
- EN 301489-3 V1.6.1
- EN 61000-3-2:2013,
- EN 61000-3-3:2013
- EN 300220-2:V3.1.1
- EN 62479:2010

### USA

- FCC & IC Rules

From:

<http://wiki.hiq-universe.com/> -

Permanent link:

[http://wiki.hiq-universe.com/doku.php?id=en:hiq\\_hw:en-ws-iq&rev=1591006584](http://wiki.hiq-universe.com/doku.php?id=en:hiq_hw:en-ws-iq&rev=1591006584)

Last update: **2020/06/01 10:16**

