

# IOT Linker 2 Ethernet Port

**Advanced EDGE device. Connects Cybro, MC and RDX Charger to HIQ universe**



|                                             |                                                                                       |
|---------------------------------------------|---------------------------------------------------------------------------------------|
| Order code without Power Supply             | <b>IOT-L2-2</b>                                                                       |
| Order code with AC Power Supply 230VAC/5VDC | <b>IOT-L2-2-AC</b>                                                                    |
| Order code with DC Power Supply 24VDC/5VDC  | <b>IOT-L2-2-DC</b>                                                                    |
| License for specific IOT linker software    | <b>IOT-C2-xx; xx-version of the software</b>                                          |
| 4G LTE USB modem for IOT linker             | <b>IOT-L2-W</b>                                                                       |
| Mounting:                                   | DIN rail, (Optional wall)                                                             |
| Dimensions:                                 | 60 x 61 x 26 mm                                                                       |
| Connection:                                 | LAN Port: connects to Cybro, MC or Robotina Charger; WAN Port: uplink to HIQ Universe |

- Robust and safe connection of HIQ and 4S systems to HIQ Universe cloud platform.
- Secure access and communication (TLS encryption)
- Local data buffer, no data loss
- User data safety according to GDPR
- Secure remote access to HIQ controllers and chargers

## Technical specifications

|               |              |
|---------------|--------------|
| Power supply: | USB-C, 5V DC |
|---------------|--------------|

|                 |                                                               |
|-----------------|---------------------------------------------------------------|
| Storage:        | MicroSD x1 for external storage up to 128GB                   |
| USB Host:       | 1x 2.0 Type-A                                                 |
| Network:        | 2x 10/100/1000M Ethernet                                      |
| Working temp.:  | 0°C to 80°C                                                   |
| 4G connection : | USB                                                           |
| Software :      | IOT linker system software is sold separately on MicroSD card |

## Mounting

### DIN Rail, Optional Wall



From:  
<https://wiki.hiq-universe.com/> -

Permanent link:  
[https://wiki.hiq-universe.com/doku.php?id=en:hiq\\_hw:iot\\_linker](https://wiki.hiq-universe.com/doku.php?id=en:hiq_hw:iot_linker)

Last update: **2023/01/28 21:15**

