

IOT Linker 2 Ethernet Port

Advanced EDGE device. Connects Cybro, MC and Robotina Charger to HIQ universe



Order code without Power Supply	IOT-L2-2
Order code with AC Power Supply 230VAC/5VDC	IOT-L2-2-AC
Order code with DC Power Supply 24VDC/5VDC	IOT-L2-2-DC
License for specific IOT linker software	IOT-C2-xx; xx-version of the software
4G LTE USB modem for IOT linker	IOT-L2-W
Mounting:	DIN rail, (Optional wall)
Dimensions:	60 x 61 x 26 mm
Connection:	LAN Port: connects to Cybro, MC or Robotina Charger; WAN Port: uplink to HIQ Universe

- Robust and safe connection of HIQ and 4S systems to HIQ Universe cloud platform.
- Secure access and communication (TLS encryption)
- Local data buffer, no data loss
- User data safety according to GDPR
- Secure remote access to HIQ controllers and chargers

Technical specifications

Power supply:	USB-C, 5V DC
Storage:	MicroSD x1 for external storage up to 128GB
USB Host:	1x 2.0 Type-A
Network:	2x 10/100/1000M Ethernet
Working temp.:	0°C to 40°C
4G connection :	USB
Software :	IOT linker system software is sold separately on MicroSD card

Mounting

DIN Rail, Optional Wall



From:
<https://wiki.hiq-universe.com/> -

Permanent link:
https://wiki.hiq-universe.com/doku.php?id=en:hiq_hw:iot_linker&rev=1670582949

Last update: **2022/12/09 10:49**

