

Master Controller

Advanced Controller



Model number:	MC-24-01	24 VAC, 11 IO, Enocean, 2 × RS232, RS485, IEX2 terminals
	MC-24-02	24 VAC, 11 IO, 2 × RS232, RS485, IEX2 terminals
	MC-24-03	24 VAC, 11 IO, Enocean, 2 × RS232, isolated RS485, IEX2 terminals
	MC-24-04	24 VAC, 11 IO, 2 × RS232, isolated RS485, IEX2 terminals
Mounting:	DIN rail, 6M, 106mm	
Dimensions:	106x108x58mm	

Features

- 3 digital inputs
- 4 relay outputs 8 A
- 4 universal inputs/outputs
- Ethernet, USM, IEX-2, 2×RS232, 1×RS485 (optional isolated)
- Enocean gateway (optional)
- 24 VDC power supply

Safety standards

EN 50081-1, EN 61000-6-2, EN 61131-1, EN 61131-2, EN 61000-3-2, EN 61000-3-3

Technical specification

Relay outputs:	8A/250V
Communication:	Ethernet, 2x RS232, 1x RS485, IEX-2 bus
Nominal power rating:	24 VDC
Power consumption:	50 mA (no load), 180 mA max
Ingress protection:	IP20
Operating temperature:	0..50°C
Storage temperature:	-40..85°C
Relative humidity:	0..85% n/c

Terminals

From:
<http://wiki.hiq-universe.com/> -

Permanent link:
http://wiki.hiq-universe.com/doku.php?id=en:hiq_hw:mc-24&rev=1566215747

Last update: **2019/08/19 11:55**

