

Wireless connection

Wireless power and signal lock conection



Model number:	EL-PW	Wireless lock connection
---------------	--------------	--------------------------

Technical specifications

Power supply:	12 / 24 VDC field selectable.
	Set switch to 24DCV!

Wiring

Frame side

EL-PW	CR-W2-IQ		MC-230-3W		Notes
	1st	2nd	1st	2nd	

RD	-	-	+24VDC lock power supply
BK	-	-	GND lock power supply
GN	-	-	Momentary open (fixed 3s)
YE	C0	C0	Open common
BN	QX0	QX1	Momentary open (max 90s)
BU	IW0	IW2	Door status
GY	C0	C5	
YE	-	-	Error status
WH	-	-	
BK-WH	-	-	NC switch 1
GY-WH	-	-	COM switch 1
VT-WH	-	-	NO switch 1
GN-WH	-	-	NC switch 2
BK-YE	-	-	COM switch 2
PK	-	-	NO switch 2

Door side

EL-PW	EL-ML	Notes
OG	RD	Unlock signal
BK	BK	
BU	VT	Switch 1 - REX
GY	PK	
YE	GN	Switch 2 - Deadbolt
WH	BN	

[sta_-_powerkack_installation_manual.pdf](#)

From:
<https://wiki.hiq-universe.com/> -

Permanent link:
https://wiki.hiq-universe.com/doku.php?id=en:hiq_hw:wireless-connection

Last update: **2020/04/10 10:47**

