

Motion sensor

Enocean wireless motion sensor



| | | |
|---------------|---------------------------|--------------------|
| Model number: | <input type="checkbox"/> | EN-MS-WT-IQ |
| Mounting: | In-field; on wall | |
| Dimensions: | 65 x 65 x 39 mm | |
| Connection: | Wireless Enocean | |
| | MC-230-01 | |
| | MC-230-03 | |
| | MC-24-01 | |
| | MC-24-03 | |
| | MC-24-05 | |

Applications

- Motion detector
- Ready light
- Intrusion detector
- Lighting control

- Hotel GRMS

Features

- Small visible surface
- Easy mount
- Wireless

Technical specifications

| | |
|--------------------------|--|
| Power supply: | Battery CR123A 3V - 5 years battery lifetime |
| Range: | Up to 30 m indoor |
| Detection range: | Up to 5 m indoor |
| Lux sensing: | 0 to 1000 Lux |
| Operational temperature: | 0°C to 40° |
| EEP (EnOcean Profile): | A5-07-03 |
| Dimensions : | 65 x 65 x 30 mm |

Detection pattern and range

Certifications and standards

Europe

- EN 60950-1:2006+A11:2009
- +A1:2010+A12:2011+A2:2013
- EN 301 489-1 V2.2.0
- EN 301 489-3 V2.1.1
- EN 300 220-2 V3.1.1
- EN 62479:2010

From:

<http://wiki.hiq-universe.com/> -

Permanent link:

http://wiki.hiq-universe.com/doku.php?id=en:ms_main:en-ms-wt-iq&rev=1589111554

Last update: **2020/05/10 11:52**

