

QR code reader

QR code and RFID reader



| | | |
|---------------|---------------------------------|------------------------------------|
| Model number: | QR-FR-C | QR code and RFID EM 125 kHz, black |
| Mounting: | Field, UK rectangular flush box | |
| Connection: | Wiegand | |

Technical specifications

| | |
|-------------------|-------------------------|
| Power supply: | 12 VDC |
| Reading Distance: | QR 0-20 cm, RFID 3-6 cm |
| Card interface: | EM 125 kHz |
| Output Interface: | Wiegand 26 / 34 |

Wiring

| QR-FR-C | CR-W2-IQ | | MC-230-3W | |
|---------|----------|------|-----------|------|
| | 1st | 2nd | 1st | 2nd |
| +12V | +12V | | +12V | |
| GND | GND | | GND | |
| D0 | D0-0+1 | | D0 | |
| D1 | D1-0 | D1-1 | D1-0 | D1-1 |
| GN | GN-0 | GN-1 | GN-0 | GN-1 |
| B | / | | / | |
| Tx | / | | / | |
| Rx | / | | / | |
| S+ | / | | / | |
| S- | / | | / | |

Dimensions



From:

<http://wiki.hiq-universe.com/> -

Permanent link:

http://wiki.hiq-universe.com/doku.php?id=en:ms_main:qr-fr-c&rev=1637174638

Last update: **2021/11/17 18:43**

