

# IOT Linker 2 Ethernet Port

connected home for future connected services



Order code (without Power Supply):	<b>IOT-L2-2</b>
Order code (with AC Power Supply 230VAC/5VDC):	<b>IOT-L2-2-AC</b>
Order code (with DC Power Supply 24VDC/5VDC):	<b>IOT-L2-2-DC</b>
Mounting:	DIN rail, wall
Dimensions:	60 x 61 x 26 mm
Connection:	Ethernet Port 1: connects to Cybro Ethernet Port 2: uplink to HIQ Universe

- Robust and safe connection of HIQ and 4S systems to HIQ Universe cloud platform.
- Secure access and communication (TLS encryption)
- Local data buffer, no data loss
- User data safety according to GDPR
- Secure remote access to HIQ MC controllers

## Technical specifications

Power supply:	Micro USB, 5V DC
Storage:	MicroSD x1 for external storage up to 128GB
USB Host:	1x 2.0 Type-A
Network:	2x 10/100/1000M Ethernet
Working temp.:	0°C to 40°C
4G connection :	USB
Software :	IOT linker system software is sold separately on MicroSD card

## Mounting

### DIN Rail or Wall



From:  
<https://wiki.hiq-universe.com/> -

Permanent link:  
[https://wiki.hiq-universe.com/doku.php?id=iot\\_linker&rev=1606305896](https://wiki.hiq-universe.com/doku.php?id=iot_linker&rev=1606305896)

Last update: **2020/11/25 12:04**

