IOT Linker 2 Ethernet Port

connected home for future connected services



Order code without Power Supply:	**IOT-L2-2**
Order code with AC Power Supply 230VAC/5VDC:	**IOT-L2-2-AC**
Order code with DC Power Supply 24VDC/5VDC:	**IOT-L2-DC**
License for specific IOT linker software:	**IOT-C2-xx xx-version of software**
USB wireless modem for IOT linker	IOT-L2-W
Mounting:	DIN rail, wall
Dimensions:	60 x 61 x 26 mm
Connection:	Ethernet Port 1: connects to Cybro or MC Controller Ethernet Port 2: uplink to HIQ Universe

- Robust and safe connection of HIQ and 4S systems to HIQ Universe cloud platform.
- Secure access and communication (TLS encryption)
- Local data buffer, no data loss
- User data safety according to GDPR
- Secure remote access to HIQ MC controllers

Technical specifications

Power supply:	Micro USB, 5V DC
Storage:	MicroSD x1 for external storage up to 128GB
USB Host:	1x 2.0 Type-A
Network:	2x 10/100/1000M Ethernet
Working temp.:	0℃ to 40℃
4G connection :	USB
Software :	IOT linker system software is sold separately on MicroSD card

Mounting

DIN Rail or Wall





From:
https://wiki.hiq-universe.com/ -

Permanent link:
https://wiki.hiq-universe.com/doku.php?id=iot_linker&rev=1621490169

Last update: **2021/05/20 05:56**